











1軸、2軸、3軸加速度センサ									デモ機	
SCA610 / 620 / 630	SCA810 / 820 / 830	SCA1000 / 1020	SCA2100/2110/2120	CMA3000-A01/D01	SCA3060 / SCA3100	SCA8X0 / 21X0 / 3100				
      										
センサ型式	軸	レンジ	供給電源	出力	オフセット温度特性	感度	帯域幅	寸法	SCAXXX0-PWB	
SCA100T-D07	2軸 XY	±12g	5V	Analog/SPI	±200mg (-40...+125°C)	0.17V/g	400Hz	15.58x11.31x5.08		
SCA610-CAHH1G	1軸 X	±0.5g	5V	Analog	±2.86° (-40...+125°C)	4V/g	18Hz	10.48x11.31x5.08		
SCA610-CA1H1G	1軸 X	±1g	5V	Analog	±2.86° (-40...+125°C)	2V/g	18Hz	10.48x11.31x5.08		
SCA610-C23H1A	1軸 X	±1.5g	5V	Analog	±125mg (-40...+125°C)	1.33V/g	50Hz	10.48x11.31x5.08		
SCA610-C28H1A	1軸 X	±1.7g	5V	Analog	±125mg (-40...+125°C)	1.2V/g	50Hz	10.48x11.31x5.08		
SCA620-CF8H1A	1軸 Z	±1.5g	5V	Analog	±125mg (-40...+125°C)	1.2V/g	50Hz	10.48x11.31x5.08		
SCA630-EDCV1B	1軸 Y	±13.3g	5V	Analog	±870mg (-40...+125°C)	0.15V/g	400Hz	10.48x11.31x5.08		
SCA810-D01	1軸 X	±2g	3.3V	PWM/SPI	±70mg (-40...+125°C)	900 Count/g	50Hz	8.6x7.6x3.3		CMA3000-D01 DEMO
SCA820-D03	1軸 Z	±2g	3.3V	PWM/SPI	±70mg (-40...+125°C)	900 Count/g	50Hz	8.6x7.6x3.3		
SCA830-D05	1軸 Y	±2g	3.3V	PWM/SPI	±70mg (-40...+125°C)	900 Count/g	50Hz	8.6x7.6x3.3		
SCA830-D06	1軸 Y	±2g	3.3V	PWM/SPI	±40mg (-40...+125°C)	900 Count/g	50Hz	8.6x7.6x3.3		
SCA1000-D01	2軸 XY	±1.7g	5V	Analog/SPI	±100mg (-40...+125°C)	1.2V/g	50Hz	15.58x11.31x5.08		
SCA1000-N1000070	2軸 XY	±4g	5V	Analog/SPI	±60mg (-40...+125°C)	0.55V/g	115Hz	15.58x11.31x5.08		
SCA1020-D02	2軸 YZ	±1.7g	5V	Analog/SPI	±100mg (-40...+125°C)	1.2V/g	50Hz	15.58x11.31x5.08		
SCA2100-D01	2軸 XY	±2g	3.3V	SPI	±70mg (-40...+125°C)	900 Count/g	45Hz	8.6x7.6x3.3		
SCA2100-D02	2軸 XY	±2g	3.3V	SPI	±30mg (-40...+125°C)	900 Count/g	45Hz	8.6x7.6x3.3		
SCA2110-D03	2軸 XZ	±2g	3.3V	SPI	±70mg (-40...+125°C)	900 Count/g	45Hz	8.6x7.6x3.3		
SCA2120-D07	2軸 YZ	±2g	3.3V	SPI	±70mg (-40...+125°C)	900 Count/g	45Hz	8.6x7.6x3.3		
CMA3000-A01	3軸	±2g / ±8g	1.7...3.6V	Analog	±160mg (-40...+85°C)	0.55 or 0.138V/g	50Hz	2.0x2.0x0.95		
CMA3000-D01	3軸	±2g / ±8g	1.7...3.6V	SPI/I ² C	±160mg (-40...+85°C)	14 or 56 Count/g	10/40Hz	2.0x2.0x0.95		
SCA3060-D01	3軸	±2g	3.0...3.6V	SPI	±200mg (-40...+105°C)	1000 Count/g	9/35Hz	8.6x7.6x3.3		
SCA3060-D02	3軸	±2g	3.0...3.6V	I ² C	±200mg (-40...+105°C)	1000 Count/g	11/40Hz	8.6x7.6x3.3		
SCA3100-D04	3軸	±2g	1.7...3.6V	SPI	±70mg (-40...+125°C)	900 Count/g	45Hz	8.6x7.6x3.3		
SCA3100-D07	3軸	±6g	3.3V	SPI	±70mg (-40...+125°C)	650 Count/g	45Hz	8.6x7.6x3.3		
									CMA3000-PWB	

デモ機	軸	レンジ	供給電源	出力
SCA8X0 D0X DEMO	1軸	±2g	USBより	PCとUSB 接続
SCA21X0 D0X DEMO	2軸	±2g	USBより	PCとUSB 接続
SCA3100 D0X DEMO	3軸	±2g / 6g	USBより	PCとUSB 接続
CMA3000 D0X DEMO	3軸	±2g / 8g	USBより	PCとUSB 接続

* 仕様は予告無く変更されることがあります。